



II NanoFrontMag Scientific Workshop

Mapping of magnetic quantities across oxide interfaces via high resolution energy-loss magnetic circular dichroism

Maria Varela

Universidad Complutense de Madrid. 28040 Madrid, Spain

Complex oxides with a perovskite structure show a wide range of interesting properties due to a strong interplay and competition between lattice, spin, and charge degrees of freedom. This is particularly the case when obtained in the form of thin films or heterostructures, where novel macroscopic functionalities may arise. In this talk we will apply atomic resolution aberration corrected scanning transmission electron microscopy (STEM) and electron energy-loss spectroscopy (EELS) to the study of the structure and properties of magnetic oxide heterostructures. A first example of application involves local measurements of electronic and magnetic properties of ferromagnetic manganite $\text{La}_{0.7}\text{Sr}_{0.3}\text{MnO}_3$ (LSMO) epitaxial ultrathin films grown by high-pressure O_2 sputtering on single crystal SrTiO_3 (STO) substrates. We will combine STEM-EELS with density-functional calculations to study local structural distortions and electronic phenomena associated with interfacial magnetism. Atomic resolution images exhibit an increase of the out-of-plane lattice parameter at the LSMO/STO interface plane, pointing to a local reconstruction of the charge density and, hence, physical properties. We use energy-loss magnetic chiral dichroism (EMCD) [1], a technique directly sensitive to the local magnetic moment, to track magnetic quantities across the interface with sub-unit cell resolution. The dichroic signal at both the Mn L_{2,3} and the Ti L_{2,3} edges is enhanced near the interface, pointing to a local increase of the Mn and Ti magnetic moments. These results agree with density-functional theory simulations including interfacial oxygen vacancies, which enhance charge transfer and antiferromagnetic coupling between the Ti and the Mn. A second example can be found in the study of the electronic and magnetic properties of multiferroic interfaces where ultrathin ferroelectric BaTiO_3 (BTO) barriers are sandwiched between ferromagnetic LSMO electrodes. Real space measurements of local polarization obtained through the analysis of atomic resolution annular bright field images [3] will be compared to magnetic quantities measured from spatially resolved EMCD. Work done in collaboration with Javier Grandal, Juan I. Beltran, Gabriel Sanchez-Santolino, Fernando Gallego, Javier Tornos, Carlos Leon, Jacobo Santamaria and M. Carmen Muñoz.

References:

- [1] P. Schattschneider et al., Nature 441 (2006) pp. 486-488.
- [2] J. Salafranca et al., Nanoletters 12 (2012), pp. 2499-2503.
- [3] G. Sanchez-Santolino et al., Nature Nanotechnology 12, (2017) 655-662.
- [4] Research at UCM sponsored by Fundación BBVA and Spanish MINECO/FEDER MAT2015-66888-C3-1-R & MAT2015-66888-C3-3-R and by the ERC Proof of Concept Grant POLAR-EM.